



WARKWORTH MANUAL iDIMMERS & PROGRAMMABLE TIMER CONTROL

EASY TO INSTALL AND CONNECT	REPLICATES DAWN TO DUSK LIGHTING
DIM FROM 0-100% WITHOUT FLICKER	OVER TEMPERATURE PROTECTION
SAFETY DIM TO 0% DRY SWITCH CONTACT	OVER CURRENT PROTECTION
ANTI-6KV LIGHTNING SURGE	SHORT CIRCUIT PROTECTION
SUPPORT EXTERNAL 0-10V SIGNAL SYSTEMS CONTROL	OVER VOLTAGE & OVER POWER PROTECTION
REDUCE HARMONIC PEAK WAVE	5 YEAR TOTAL PRODUCT WARRANTY

1500W WARKWORTH iDIMMER 2L MANUAL CONTROL

GL7032

Input Voltage: 100-264 VAC
Frequency: 50-60Hz
220VAC Rated Wattage: 1500W
110VAC Rated Wattage: 1000W
Ambient Operating Temperature: -20°C - +50°C
Storage Temperature: -20°C - +80°C
Humidity: 20%-90% RH Non-Condensing
Product Materials: Aluminium
PF: ≥0.97
IP: 44
Weight (kg): 3



3000W WARKWORTH iDIMMER 3S MANUAL CONTROL

GL7033

Input Voltage: 100-264 VAC
Frequency: 50-60Hz
220VAC Rated Wattage: 3000W
110VAC Rated Wattage: 1500W
Ambient Operating Temperature: -20°C - +50°C
Storage Temperature: -20°C - +80°C
Humidity: 20%-90% RH Non-Condensing
Product Materials: Aluminium
PF: ≥0.97
IP: 44
Weight (kg): 5.5



WARKWORTH PROGRAMMABLE TIMER CONTROL

GL7037

Input Voltage: 100-264 VAC
Frequency: 50-60Hz
 Built In 0-10V signal
 Manual Brightness Control
 Programmable Brightness Control by Auto-Self Setting
 USB Port for Programme Update
 24 Hours per Day Lighting Programme Control
 Supports DIY Lighting Programme Setting
 5 Modes for Lighting Programme Setting
Product Materials: Aluminium
IP: 44
Weight (kg): 2

