



WARKWORTH AUTOMATIC iDIMMERS

EASY TO
INSTALL AND
CONNECT

REPLICATES
DAWN
TO DUSK
LIGHTING

DIM FROM
0-100% WITH-
OUT FLICKER

OVER
TEMPERATURE
PROTECTION

SAFETY DIM
TO 0% DRY
SWITCH
CONTACT

OVER
CURRENT
PROTECTION

ANTI-6KV
LIGHTNING
SURGE

SHORT
CIRCUIT
PROTECTION

SUPPORT
EXTERNAL
0-10V SIGNAL
SYSTEMS
CONTROL

OVER VOLTAGE
& OVER POWER
PROTECTION

REDUCE
HARMONIC
PEAK WAVE

5 YEAR
TOTAL
PRODUCT
WARRANTY

3000W WARKWORTH iDIMMER 3L AUTOMATIC CONTROL

GL7034

Input Voltage: 100-264 VAC

Frequency: 50-60Hz

220VAC Rated Wattage: 3000W

110VAC Rated Wattage: 1500W

Ambient Operating Temperature: -20°C - +50°C

Storage Temperature: -20°C - +80°C

Humidity: 20%-90% RH Non-Condensing

Product Materials: Aluminium

PF: ≥ 0.97

IP: 44

Weight (kg): 5.5

3000
WATT

IP
44

PF
0.9



4500W WARKWORTH iDIMMER 4L AUTOMATIC CONTROL

GL7036

Input Voltage: 100-264 VAC

Frequency: 50-60Hz

220VAC Rated Wattage: 4500W

110VAC Rated Wattage: 2400W

Ambient Operating Temperature: -20°C - +50°C

Storage Temperature: -20°C - +80°C

Humidity: 20%-90% RH Non-Condensing

Product Materials: Aluminium

PF: ≥ 0.97

IP: 44

Weight (kg): 8

4500
WATT

IP
44

PF
0.9

